NSN 3413-00-194-7688



Upright Drilling Machine - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3413-00-194-7688 **Mounting Type:** Floor **Electric Motor Power Rating:** 5.000 horsepower **Current Type:** Ac **Head Type:** Sliding **Fungus Resistant Treatment:** Not included **Accessory Components And Quantity:** 18 in. Rotary table 1 Radio Interference Shielding: Not provided **Rotation Reversibility Feature:** Not included Feed Type: Power **Electric Motor Horsepower Rating:** 5.000 **Spindle Quantity:** 1 Main Drive Type: Electric motor **Spindle Socket Taper Size:** 40 american standard taper **Spindle Travel Distance:** 8.000 inches **Drilling Capability:** 2 in. Drilling capacity in mild steel **Column Type: Distance From Spindle Center To Column:** 30.000 inches **Base Working Surface Type:** Slotted **Base Working Surface Shape:** Round **Base Working Surface Diameter:** 18.000 inches

Base Working Surface Mounting Location:

Base

NSN 3413-00-194-7688Upright Drilling Machine - Page 2 of 2



Maximum Distance From Chuck/spindle Nose To Base Working Surface:
26.000 inches
Head Vertical Adjustment:
22.000 inches
Spindle Type:
Tapered socket
Spindle Speed Quantity:
1
Spindle Speed Range In Rpm:
+80.0 to 4000.0
Voltage In Volts:
220.0
Phase:
Three
Special Features:
Numerical controlled system, automatic drilling, boring, tapping, milling cycle, perforated tape
Frequency In Hertz:
60.0
Reference Number Differentiating Characteristics:
As differentiated by drilling capacity, rpm spindle speed, rotary table, numerical control system
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T317-f