

View Online at <https://aerobasegroup.com/nsn/3413-00-221-8714>

Mounting Type:

Bench

Electric Motor Power Rating:

0.250 horsepower

Current Type:

Ac

Head Type:

Fixed

Fungus Resistant Treatment:

Included

Accessory Components And Quantity:

Guard 1

Radio Interference Shielding:

Provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Electric Motor Horsepower Rating:

0.250

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

Jacobs1

Spindle Travel Distance:

2.250 inches

Base Working Surface Length:

6.000 inches

Base Working Surface Width:

4.000 inches

Drilling Capability:

1/4 in mild steel

Column Type:

Round

Drill Chuck Size Accommodated:

1/4 in. Key

Distance From Spindle Center To Column:

3.000 inches

Base Working Surface Type:

Plain

Base Working Surface Shape:

Rectangular

Base Working Surface Area:

Any acceptable

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

8.500 inches

Upper Working Surface Type:

Plain

Upper Working Surface Shape:

Rectangular

Upper Working Surface Area:

Any acceptable

Upper Working Surface Length:

5.250 inches

Upper Working Surface Width:

5.000 inches

Upper Working Surface Adjustment Feature:

Not included

Upper Working Surface Vertical Adjustment:

6.000 inches

Swivel Adjustment In Deg:

180.000

Spindle Type:

Solid male tapered for drill chuck

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+750.000 to 6000.000

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

6.000 inches

Voltage In Volts:

115.000

Phase:

Single

Frequency In Hertz:

60.000

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T317-f