

View Online at <https://aerobasegroup.com/nsn/3413-00-221-8715>

Mounting Type:

Floor

Current Type:

Ac

Head Type:

Fixed

Fungus Resistant Treatment:

Not included

Accessory Components And Quantity:

Chuck /1/; drifts, drill /3/; sleeve, reducing /2/

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Power

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

No. 4 morse taper

Spindle Travel Distance:

10.500 inches

Base Working Surface Length:

17.500 inches

Base Working Surface Width:

16.250 inches

Drilling Capability:

1-1/2 in. In mild steel

Column Type:

Round

Distance From Spindle Center To Column:

10.500 inches

Base Working Surface Type:

Tee slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Mounting Location:

Located at base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

41.000 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Round

Upper Working Surface Diameter:

17.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

27.313 inches

Swivel Adjustment In Deg:

360.000

Spindle Type:

Tapered socket

Spindle Speed Quantity:

8

Spindle Speed Range In Rpm:

+23.000/+400.000

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

30.313 inches

Voltage In Volts:

220.000

Phase:

Three

Frequency In Hertz:

60.000

Departure From Cited Document:

As modified by pygq, pyht, pyhu, pyhv, pyhw, pyhx, pyhy, pyhz, pyja, pyjb, pyje

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f