

View Online at <https://aerobasegroup.com/nsn/3413-00-222-2141>

**Mounting Type:**

Floor

**Electric Motor Power Rating:**

0.500 horsepower

**Current Type:**

Ac

**Head Type:**

Sliding

**Fungus Resistant Treatment:**

Not included

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Not included

**Feed Type:**

Hand

**Electric Motor Horsepower Rating:**

0.500

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Travel Distance:**

6.000 inches

**Base Working Surface Length:**

11.000 inches

**Base Working Surface Width:**

9.000 inches

**Drilling Capability:**

1/2 in. Drilling capacity in mild steel

**Column Type:**

Round

**Drill Chuck Size Accommodated:**

1/2 in. Key

**Distance From Spindle Center To Column:**

7.000 inches

**Base Working Surface Type:**

Slotted

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Mounting Location:**

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

27.000 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Square

Upper Working Surface Length:

12.000 inches

Upper Working Surface Width:

12.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

8.250 inches

Swivel Adjustment In Deg:

360.0

Tilt Adjustment Direction And Angle In Deg:

90.0 right err-100 err-100

Head Vertical Adjustment:

8.250 inches

Spindle Type:

Threaded end for drill chuck

Spindle Speed Quantity:

5

Spindle Speed Range In Rpm:

+400.0 to 3000.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

27.000 inches

Voltage In Volts:

110.0

Phase:

Single

Frequency In Hertz:

60.0

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

**Fiig:**

T317-f