

View Online at <https://aerobasegroup.com/nsn/3413-00-222-2141>

Mounting Type:

Floor

Electric Motor Power Rating:

0.500 horsepower

Current Type:

Ac

Head Type:

Sliding

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Electric Motor Horsepower Rating:

0.500

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Travel Distance:

6.000 inches

Base Working Surface Length:

11.000 inches

Base Working Surface Width:

9.000 inches

Drilling Capability:

1/2 in. Drilling capacity in mild steel

Column Type:

Round

Drill Chuck Size Accommodated:

1/2 in. Key

Distance From Spindle Center To Column:

7.000 inches

Base Working Surface Type:

Slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

27.000 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Square

Upper Working Surface Length:

12.000 inches

Upper Working Surface Width:

12.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

8.250 inches

Swivel Adjustment In Deg:

360.0

Tilt Adjustment Direction And Angle In Deg:

90.0 right err-100 err-100

Head Vertical Adjustment:

8.250 inches

Spindle Type:

Threaded end for drill chuck

Spindle Speed Quantity:

5

Spindle Speed Range In Rpm:

+400.0 to 3000.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

27.000 inches

Voltage In Volts:

110.0

Phase:

Single

Frequency In Hertz:

60.0

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:
T317-f