

View Online at <https://aerobasegroup.com/nsn/3413-00-222-2142>

Mounting Type:

Floor

Electric Motor Power Rating:

1.000 horsepower

Current Type:

Ac

Head Type:

Sliding

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Electric Motor Horsepower Rating:

1.000

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

No. 2 morse taper

Spindle Travel Distance:

7.500 inches

Base Working Surface Length:

16.000 inches

Base Working Surface Width:

14.625 inches

Drilling Capability:

3/4 in. In mild steel, 7/8 in. In cast iron

Column Type:

Round

Distance From Spindle Center To Column:

8.000 inches

Base Working Surface Type:

Slotted

Base Working Surface Shape:

Round

Base Working Surface Area:

Any acceptable

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

45.000 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Round

Upper Working Surface Area:

Any acceptable

Upper Working Surface Diameter:

24.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

17.000 inches

Swivel Adjustment In Deg:

180.000

Tilt Adjustment Direction And Angle In Deg:

45.0 right err-100 err-100

Head Vertical Adjustment:

8.500 inches

Spindle Type:

Tapered socket

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+425.000 to 1780.000

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

30.000 inches

Voltage In Volts:

220.0 or 440.0

Phase:

Single

Frequency In Hertz:

60.000

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:
T317-f