## NSN 3413-00-222-2145



Upright Drilling Machine - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3413-00-222-2145 **Mounting Type:** Floor **Electric Motor Power Rating:** 1.000 horsepower **Current Type:** Ac **Head Type:** Sliding **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Hand **Electric Motor Horsepower Rating:** 1.000 **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Socket Taper Size:** 3 morse **Spindle Travel Distance:** 8.000 inches **Base Working Surface Length:** 21.000 inches **Base Working Surface Width:** 18.000 inches **Drilling Capability:** 1.000 in mild steel

**Column Type:** Box **Distance From Spindle Center To Column:** 8.000 inches **Base Working Surface Type:** Slotted w/coolant trough **Base Working Surface Shape:** Rectangular **Base Working Surface Area:** Any acceptable

## **NSN 3413-00-222-2145**Upright Drilling Machine - Page 2 of 2



Base Working Surface Vertical Adjustment:
17.000 inches
Base Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Base Working Surface:
21.000 inches
Head Vertical Adjustment:
8.000 inches
Spindle Type:
Tapered socket
Spindle Speed Quantity:
8
Spindle Speed Range In Rpm:
+250.0 to 1100.0
Voltage In Volts:
220.0
Phase:
Three
Special Features:
Feed type power
Frequency In Hertz:
60.0
Specification Or Standard:
2 class
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
T317-f