## NSN 3413-00-222-2149

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-00-222-2149 **Mounting Type:** Floor **Current Type:** Ac **Head Type:** Sliding **Fungus Resistant Treatment:** Not included Radio Interference Shielding: Not provided **Rotation Reversibility Feature:** Not included Feed Type: Hand **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Socket Taper Size:** No. 4 morse taper **Spindle Travel Distance:** 9.250 inches **Base Working Surface Length:** 17.000 inches **Base Working Surface Width:** 17.000 inches **Drilling Capability:** 1.500 in mild steel Column Type: Box **Distance From Spindle Center To Column:** 11.625 inches **Base Working Surface Type:** Plain w/coolant trough **Base Working Surface Shape:** Square **Base Working Surface Mounting Location:** Base Maximum Distance From Chuck/spindle Nose To Base Working Surface: 33.750 inches **Upper Working Surface Type:** 

Plain w/coolant trough

## **NSN 3413-00-222-2149**Upright Drilling Machine - Page 2 of 2



Upper Working Surface Shape:
Rectangular
Upper Working Surface Length:
21.500 inches
Upper Working Surface Width:
17.250 inches
Upper Working Surface Adjustment Feature:
Included
Upper Working Surface Vertical Adjustment:
19.000 inches
Head Vertical Adjustment:
11.000 inches
Spindle Type:
Tapered socket
Spindle Speed Quantity:
8
Spindle Speed Range In Rpm:
+300.0/+2100.0
Upper Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Upper Working Surface:
21.000 inches
Voltage In Volts:
220.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
T317-f