

View Online at <https://aerobasegroup.com/nsn/3413-00-222-2150>

Mounting Type:

Floor

Current Type:

Ac

Head Type:

Sliding

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Included

Feed Type:

Hand

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

3 morse

Spindle Travel Distance:

10.000 inches

Drilling Capability:

1.250 in mild steel

Column Type:

Box

Distance From Spindle Center To Column:

12.000 inches

Upper Working Surface Type:

Slotted w/coolant trough

Upper Working Surface Shape:

Rectangular

Upper Working Surface Length:

22.000 inches

Upper Working Surface Width:

18.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

14.000 inches

Head Vertical Adjustment:

10.000 inches

Spindle Type:

Tapered socket

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+650.0/+2004.0

Upper Working Surface Mounting Location:

Over lower round table

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

29.250 inches

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f