## NSN 3413-00-222-2151

Upright Drilling Machine - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/3413-00-222-2151

Mounting Type:
Bench
Electric Motor Power Rating:
0.500 horsepower
Current Type:
Ac
Head Type:
Radial swinging/sliding
Fungus Resistant Treatment:
Not included
Radio Interference Shielding:
Not provided
Rotation Reversibility Feature:
Not included
Feed Type:
Hand
Electric Motor Horsepower Rating:
0.500
Spindle Quantity:
1
Main Drive Type:
Electric motor
Spindle Travel Distance:
4.000 inches
Base Working Surface Length:
10.000 inches
Base Working Surface Width:
10.000 inches
Drilling Capability:
1/2 in. Drilling capacity in mild steel
Column Type:
Round
Drill Chuck Size Accommodated:
1/2 in. Key
Distance From Spindle Center To Column:
8.000 inches
Base Working Surface Type:
Slotted
Base Working Surface Shape:
Square
Base Working Surface Vertical Adjustment:
12.000 inches

## NSN 3413-00-222-2151

Upright Drilling Machine - Page 2 of 3



December 11 and
Base Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Base Working Surface:
10.000 inches
Upper Working Surface Type:
Slotted
Upper Working Surface Shape:
Square
Upper Working Surface Length:
10.000 inches
Upper Working Surface Width:
10.000 inches
Upper Working Surface Adjustment Feature:
Included
Upper Working Surface Vertical Adjustment:
12.000 inches
Swivel Adjustment In Deg:
90.0
Tilt Adjustment Direction And Angle In Deg:
90.0 left
Head Vertical Adjustment:
12.000 inches
Spindle Type:
Threaded end for drill chuck
Spindle Speed Quantity:
5
Spindle Speed Range In Rpm:
+450.0 to 5100.0
Upper Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Upper Working Surface:
8.000 inches
Voltage In Volts:
110.0
Phase:
Single
Frequency In Hertz:
60.000
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 3413-00-222-2151

Upright Drilling Machine - Page 3 of 3



Fiig:

T317-f