

View Online at <https://aerobasegroup.com/nsn/3413-00-224-7957>

Mounting Type:

Floor

Electric Motor Power Rating:

0.500 horsepower

Current Type:

Ac

Head Type:

Sliding

Fungus Resistant Treatment:

Not included

Accessory Components And Quantity:

Cup center 1, vee block center 1

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Included

Feed Type:

Hand

Electric Motor Horsepower Rating:

0.500

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

2 morse

Spindle Travel Distance:

3.750 inches

Drilling Capability:

5-1/2 in. Drilling capacity in mild steel

Column Type:

Round

Distance From Spindle Center To Column:

6.875 inches

Base Working Surface Type:

Plain

Base Working Surface Shape:

Round

Base Working Surface Area:

10.500 square inches

Base Working Surface Vertical Adjustment:

24.000 inches

Base Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

10.000 inches

Upper Working Surface Type:

Plain

Upper Working Surface Shape:

Square

Upper Working Surface Length:

11.000 inches

Upper Working Surface Width:

11.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

30.000 inches

Swivel Adjustment In Deg:

360.0

Tilt Adjustment Direction And Angle In Deg:

90.0 left

Head Vertical Adjustment:

9.500 inches

Spindle Type:

Tapered socket

Spindle Speed Quantity:

6

Spindle Speed Range In Rpm:

+620.0 to 3080.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

10.000 inches

Voltage In Volts:

220.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:
T317-f