

View Online at <https://aerobasegroup.com/nsn/3413-00-224-7957>

**Mounting Type:**

Floor

**Electric Motor Power Rating:**

0.500 horsepower

**Current Type:**

Ac

**Head Type:**

Sliding

**Fungus Resistant Treatment:**

Not included

**Accessory Components And Quantity:**

Cup center 1, vee block center 1

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Included

**Feed Type:**

Hand

**Electric Motor Horsepower Rating:**

0.500

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Socket Taper Size:**

2 morse

**Spindle Travel Distance:**

3.750 inches

**Drilling Capability:**

5-1/2 in. Drilling capacity in mild steel

**Column Type:**

Round

**Distance From Spindle Center To Column:**

6.875 inches

**Base Working Surface Type:**

Plain

**Base Working Surface Shape:**

Round

**Base Working Surface Area:**

10.500 square inches

**Base Working Surface Vertical Adjustment:**

24.000 inches

**Base Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Base Working Surface:**

10.000 inches

**Upper Working Surface Type:**

Plain

**Upper Working Surface Shape:**

Square

**Upper Working Surface Length:**

11.000 inches

**Upper Working Surface Width:**

11.000 inches

**Upper Working Surface Adjustment Feature:**

Included

**Upper Working Surface Vertical Adjustment:**

30.000 inches

**Swivel Adjustment In Deg:**

360.0

**Tilt Adjustment Direction And Angle In Deg:**

90.0 left

**Head Vertical Adjustment:**

9.500 inches

**Spindle Type:**

Tapered socket

**Spindle Speed Quantity:**

6

**Spindle Speed Range In Rpm:**

+620.0 to 3080.0

**Upper Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Upper Working Surface:**

10.000 inches

**Voltage In Volts:**

220.0

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**  
T317-f