

View Online at <https://aerobasegroup.com/nsn/3413-00-240-6151>

Mounting Type:

Floor

Current Type:

Ac

Head Type:

Fixed

Fungus Resistant Treatment:

Included

Accessory Components And Quantity:

Chuck, 3-jaw, 0 to 1/2 in. W/key and taper shank to fit no. 4 taper-1 ea; drifts, drill, american standard taper no. 2, 3, and 4-1 ea; drill set, twist drill, straight shank, high speed, 1/4 to 1/2 in. In 1/64 in. Increments-2 sets; drill set, twist drill, taper shank, high speed 1/2 to 1 in. In 1/16 in. Increments-1 set; drill set, twist drill, taper shank, high speed to 1 to 1-1/2 in. In 1/16 in. Increments-1 set; sleeve, reducing, no. 4 to no. 2 american standard taper-1 ea; sleeve, reducing, no. 4 to no. 3 american standard taper-1 ea

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Power

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

No. 4 american standard taper

Spindle Travel Distance:

9.000 inches

Drilling Capability:

1-1/2 in. In cast iron

Column Type:

Round

Distance From Spindle Center To Column:

10.500 inches

Base Working Surface Type:

Slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

40.000 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Round

Upper Working Surface Diameter:

16.000 inches

Upper Working Surface Adjustment Feature:

Included

Swivel Adjustment In Deg:

360.000

Spindle Type:

Tapered socket

Spindle Speed Quantity:

8

Spindle Speed Range In Rpm:

+34.0/+405.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

26.000 inches

Voltage In Volts:

208.000

Phase:

Three

Special Features:

Second upper working surface type, drill

Frequency In Hertz:

60.000

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f