

View Online at <https://aerobasegroup.com/nsn/3413-00-240-6151>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Head Type:**

Fixed

**Fungus Resistant Treatment:**

Included

**Accessory Components And Quantity:**

Chuck, 3-jaw, 0 to 1/2 in. W/key and taper shank to fit no. 4 taper-1 ea; drifts, drill, american standard taper no. 2, 3, and 4-1 ea; drill set, twist drill, straight shank, high speed, 1/4 to 1/2 in. In 1/64 in. Increments-2 sets; drill set, twist drill, taper shank, high speed 1/2 to 1 in. In 1/16 in. Increments-1 set; drill set, twist drill, taper shank, high speed to 1 to 1-1/2 in. In 1/16 in. Increments-1 set; sleeve, reducing, no. 4 to no. 2 american standard taper-1 ea; sleeve, reducing, no. 4 to no. 3 american standard taper-1 ea

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Not included

**Feed Type:**

Power

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Socket Taper Size:**

No. 4 american standard taper

**Spindle Travel Distance:**

9.000 inches

**Drilling Capability:**

1-1/2 in. In cast iron

**Column Type:**

Round

**Distance From Spindle Center To Column:**

10.500 inches

**Base Working Surface Type:**

Slotted

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Mounting Location:**

Base

**Maximum Distance From Chuck/spindle Nose To Base Working Surface:**

40.000 inches

**Upper Working Surface Type:**

Slotted

**Upper Working Surface Shape:**

Round

**Upper Working Surface Diameter:**

16.000 inches

**Upper Working Surface Adjustment Feature:**

Included

**Swivel Adjustment In Deg:**

360.000

**Spindle Type:**

Tapered socket

**Spindle Speed Quantity:**

8

**Spindle Speed Range In Rpm:**

+34.0/+405.0

**Upper Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Upper Working Surface:**

26.000 inches

**Voltage In Volts:**

208.000

**Phase:**

Three

**Special Features:**

Second upper working surface type, drill

**Frequency In Hertz:**

60.000

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T317-f