

View Online at <https://aerobasegroup.com/nsn/3413-00-242-3460>

Mounting Type:

Floor

Electric Motor Power Rating:

2.000 horsepower

Current Type:

Ac

Head Type:

Sliding

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

No. 4 morse taper

Spindle Travel Distance:

8.750 inches

Base Working Surface Length:

16.000 inches

Base Working Surface Width:

16.000 inches

Drilling Capability:

1-1/4 in. In mild steel

Column Type:

Round

Distance From Spindle Center To Column:

11.000 inches

Base Working Surface Type:

Slotted w/coolant trough

Base Working Surface Shape:

Square

Base Working Surface Mounting Location:

Located at base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

43.500 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Round

Upper Working Surface Diameter:

19.500 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

20.000 inches

Swivel Adjustment In Deg:

180.000

Tilt Adjustment Direction And Angle In Deg:

90.0 right

Head Vertical Adjustment:

10.000 inches

Spindle Type:

Tapered socket

Spindle Speed Quantity:

8

Spindle Speed Range In Rpm:

+65.000 to 1350.000

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

27.500 inches

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.000

Reference Number Differentiating Characteristics:

Qbup, pygs, pygt, pygu, pygw, pygx, qbuq, pygy, pygz, pyha, pyhb, pyhc, pyhd, pyhe, pyhf, pyhh, pyhj, pyhk, qbum

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f