

View Online at <https://aerobasegroup.com/nsn/3413-00-242-3469>

Mounting Type:

Floor

Electric Motor Power Rating:

0.500 horsepower

Current Type:

Ac

Head Type:

Radial swinging/sliding

Fungus Resistant Treatment:

Not included

Accessory Components And Quantity:

Belt v nsn 3030-00-528-4754 1; cord 15 ft 1; cord grip plug polarized 3 pole 1; drill chuck 1/2 in. With a no. 2 morse taper shank 1

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

2 morse

Spindle Travel Distance:

4.000 inches

Base Working Surface Length:

10.000 inches

Base Working Surface Width:

8.000 inches

Drilling Capability:

1/2 in. Drilling capacity in cast iron

Column Type:

Round

Distance From Spindle Center To Column:

7.500 inches

Base Working Surface Type:

Slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

44.000 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Rectangular

Upper Working Surface Length:

11.000 inches

Upper Working Surface Width:

10.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

38.000 inches

Swivel Adjustment In Deg:

360.0

Tilt Adjustment Direction And Angle In Deg:

90.0 right

Head Vertical Adjustment:

44.000 inches

Spindle Type:

Tapered socket

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+425.0 to 4000.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

38.000 inches

Voltage In Volts:

230.0

Phase:

Single

Frequency In Hertz:

60.0

Specification Or Standard:

2 type and a style and 1 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f