

View Online at <https://aerobasegroup.com/nsn/3413-00-242-3474>

**Mounting Type:**

Bench

**Electric Motor Power Rating:**

0.333 horsepower

**Current Type:**

Ac

**Head Type:**

Radial swinging/sliding

**Fungus Resistant Treatment:**

Not included

**Accessory Components And Quantity:**

1 cord, 15 ft lg, 1 cord grip plug, polarized 3 pole

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Not included

**Feed Type:**

Hand

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Travel Distance:**

4.000 inches

**Base Working Surface Length:**

7.000 inches

**Base Working Surface Width:**

10.000 inches

**Drilling Capability:**

1/2 in. Drilling capacity in cast iron, 3/8 in. Drilling capacity in steel

**Column Type:**

Round

**Drill Chuck Size Accommodated:**

1/2 in. Key

**Distance From Spindle Center To Column:**

7.000 inches

**Base Working Surface Type:**

Slotted

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Mounting Location:**

Located on base

**Upper Working Surface Type:**

Slotted

**Upper Working Surface Shape:**

Square

**Upper Working Surface Length:**

10.000 inches

**Upper Working Surface Width:**

10.000 inches

**Upper Working Surface Adjustment Feature:**

Included

**Swivel Adjustment In Deg:**

360.000

**Tilt Adjustment Direction And Angle In Deg:**

90.0 right

**Spindle Type:**

Solid male tapered for drill chuck

**Spindle Speed Quantity:**

4

**Spindle Speed Range In Rpm:**

+470.0 to 1950.0

**Upper Working Surface Mounting Location:**

Column

**Voltage In Volts:**

110.000

**Phase:**

Single

**Frequency In Hertz:**

60.000

**Specification Or Standard:**

1 class and 14 size

**Departure From Cited Designator:**

As modified by drilling capability, spindle speed range in rpm, head type, swive adjustment in deg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T317-f