

View Online at <https://aerobasegroup.com/nsn/3413-00-242-3474>

Mounting Type:

Bench

Electric Motor Power Rating:

0.333 horsepower

Current Type:

Ac

Head Type:

Radial swinging/sliding

Fungus Resistant Treatment:

Not included

Accessory Components And Quantity:

1 cord, 15 ft lg, 1 cord grip plug, polarized 3 pole

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Travel Distance:

4.000 inches

Base Working Surface Length:

7.000 inches

Base Working Surface Width:

10.000 inches

Drilling Capability:

1/2 in. Drilling capacity in cast iron, 3/8 in. Drilling capacity in steel

Column Type:

Round

Drill Chuck Size Accommodated:

1/2 in. Key

Distance From Spindle Center To Column:

7.000 inches

Base Working Surface Type:

Slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Mounting Location:

Located on base

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Square

Upper Working Surface Length:

10.000 inches

Upper Working Surface Width:

10.000 inches

Upper Working Surface Adjustment Feature:

Included

Swivel Adjustment In Deg:

360.000

Tilt Adjustment Direction And Angle In Deg:

90.0 right

Spindle Type:

Solid male tapered for drill chuck

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+470.0 to 1950.0

Upper Working Surface Mounting Location:

Column

Voltage In Volts:

110.000

Phase:

Single

Frequency In Hertz:

60.000

Specification Or Standard:

1 class and 14 size

Departure From Cited Designator:

As modified by drilling capability, spindle speed range in rpm, head type, swive adjustment in deg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T317-f