

View Online at <https://aerobasegroup.com/nsn/3413-00-243-1441>

Mounting Type:

Floor

Electric Motor Power Rating:

5.0 horsepower

Current Type:

Ac

Accessory Components And Quantity:

Drills, jobbers straight shank high speed 1/8 in. To 1/2 in. By 64ths, 2 sets; drills asa taper shank high speed 1/2 in. To 1 in. By 16ths, 2 sets; drills asa taper shank, high speed 1 in. To 1-1/2 in. By 8ths, 2 sets; sleeve reducing asa no. 4 taper to no. 3 taper, 1; sleeve reducing asa no. 4 taper to no. 2 taper, 1; sleeve reducing asa no. 4 taper to no. 1 taper, 1; table, plain box type 1

Main Drive Type:

Electric motor

Arm Size:

4.000 feet

Column Diameter:

9.000 inches

Spindle Socket Taper Size:

4 morse

Spindle Travel Distance:

10.000 inches

Maximum Distance From Spindle Center To Column:

48.000 inches

Minimum Distance From Spindle Center To Column:

13.000 inches

Maximum Distance From Spindle Nose To Base:

50.000 inches

Minimum Distance From Spindle Nose To Base:

16.000 inches

Head Travel Distance On Arm:

37.000 inches

Base Working Surface Length:

53.000 inches

Base Working Surface Width:

30.000 inches

Drilling Capability:

1-3/4 in. Drill capacity in mild steel

Spindle Speed Quantity:

9

Spindle Speed Range In Rpm:

+90.0 to 1500.0

Voltage In Volts:

208.0

Phase:

Three

Special Features:

Fungus resistance; radio interference suppression across the line magnetic starter

Frequency In Hertz:

60.0

Specification Or Standard:

A6 size

Departure From Cited Document:

Akyd and feat

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T317-e