

View Online at <https://aerobasegroup.com/nsn/3413-00-294-9573>

Mounting Type:

Floor

Electric Motor Power Rating:

0.750 horsepower

Current Type:

Ac

Head Type:

Radial swinging/sliding

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Electric Motor Horsepower Rating:

0.750

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

No. 3 morse taper

Spindle Travel Distance:

5.000 inches

Base Working Surface Length:

12.000 inches

Base Working Surface Width:

11.000 inches

Drilling Capability:

1 in. In cast iron

Column Type:

Round

Distance From Spindle Center To Column:

9.000 inches

Base Working Surface Type:

Slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Area:

Any acceptable

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

50.000 inches

Upper Working Surface Type:

Plain

Upper Working Surface Shape:

Rectangular

Upper Working Surface Area:

Any acceptable

Upper Working Surface Length:

Any acceptable

Upper Working Surface Width:

Any acceptable

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

32.000 inches

Swivel Adjustment In Deg:

360.000

Tilt Adjustment Direction And Angle In Deg:

90.0 right err-100 err-100

Head Vertical Adjustment:

32.000 inches

Spindle Type:

Tapered socket

Spindle Speed Quantity:

5

Spindle Speed Range In Rpm:

+400.000 to 3000.000

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

32.000 inches

Voltage In Volts:

110.000

Phase:

Single

Frequency In Hertz:

60.000

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T317-f