

View Online at <https://aerobasegroup.com/nsn/3413-00-517-1061>

Mounting Type:

Floor

Electric Motor Power Rating:

3.000 horsepower

Current Type:

Ac

Head Type:

Sliding

Fungus Resistant Treatment:

Included

Accessory Components And Quantity:

Chuck 1; drifts, drill 3; sleeve, reducing 2

Radio Interference Shielding:

Provided

Rotation Reversibility Feature:

Not included

Feed Type:

Power

Electric Motor Horsepower Rating:

3.000

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

No. 4 morse taper

Spindle Travel Distance:

6.875 inches

Base Working Surface Length:

16.000 inches

Base Working Surface Width:

16.000 inches

Drilling Capability:

1-1/2 in. In mild steel

Column Type:

Round

Distance From Spindle Center To Column:

11.000 inches

Base Working Surface Type:

Slotted w/coolant trough

Base Working Surface Shape:

Square

Base Working Surface Area:

Any acceptable

Base Working Surface Mounting Location:

Located at base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

43.000 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Round

Upper Working Surface Area:

Any acceptable

Upper Working Surface Diameter:

17.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

20.000 inches

Swivel Adjustment In Deg:

360.000

Tilt Adjustment Direction And Angle In Deg:

40.0 right

Head Vertical Adjustment:

10.000 inches

Spindle Type:

Tapered socket

Spindle Speed Quantity:

8

Spindle Speed Range In Rpm:

+75.000 to 1500.000

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

27.000 inches

Voltage In Volts:

220.000

Phase:

Single/three

Frequency In Hertz:

60.000

Departure From Cited Document:

Mil-d-3141

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T317-f

Mil-std (military Standard):

Mil-d-3141 spec.