

View Online at <https://aerobasegroup.com/nsn/3413-00-528-1929>

Mounting Type:

Floor

Electric Motor Power Rating:

2.000 horsepower

Current Type:

Ac

Head Type:

Sliding

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Electric Motor Horsepower Rating:

2.000

Spindle Quantity:

6

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

None

Spindle Travel Distance:

8.000 inches

Base Working Surface Length:

20.000 inches

Base Working Surface Width:

14.000 inches

Drilling Capability:

3/4 in. In mild steel

Column Type:

Round

Drill Chuck Size Accommodated:

1/2 in. Key chuck size 34b; 5/8 in. Key chuck size 38. 3/4 in. Key chuck size 36b

Distance From Spindle Center To Column:

12.000 inches

Base Working Surface Type:

Plain

Base Working Surface Shape:

Rectangular

Base Working Surface Area:

Any acceptable

Base Working Surface Mounting Location:

Located at base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

31.500 inches

Upper Working Surface Type:

Plain w/coolant trough

Upper Working Surface Shape:

Rectangular

Upper Working Surface Length:

33.000 inches

Upper Working Surface Width:

17.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

18.000 inches

Head Vertical Adjustment:

8.000 inches

Spindle Type:

Threaded end for drill chuck

Spindle Speed Quantity:

12

Spindle Speed Range In Rpm:

+225.000 to 300.000

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

25.000 inches

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.000

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f