

View Online at <https://aerobasegroup.com/nsn/3413-00-528-1929>

**Mounting Type:**

Floor

**Electric Motor Power Rating:**

2.000 horsepower

**Current Type:**

Ac

**Head Type:**

Sliding

**Fungus Resistant Treatment:**

Not included

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Not included

**Feed Type:**

Hand

**Electric Motor Horsepower Rating:**

2.000

**Spindle Quantity:**

6

**Main Drive Type:**

Electric motor

**Spindle Socket Taper Size:**

None

**Spindle Travel Distance:**

8.000 inches

**Base Working Surface Length:**

20.000 inches

**Base Working Surface Width:**

14.000 inches

**Drilling Capability:**

3/4 in. In mild steel

**Column Type:**

Round

**Drill Chuck Size Accommodated:**

1/2 in. Key chuck size 34b; 5/8 in. Key chuck size 38. 3/4 in. Key chuck size 36b

**Distance From Spindle Center To Column:**

12.000 inches

**Base Working Surface Type:**

Plain

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Area:**

Any acceptable

**Base Working Surface Mounting Location:**

Located at base

**Maximum Distance From Chuck/spindle Nose To Base Working Surface:**

31.500 inches

**Upper Working Surface Type:**

Plain w/coolant trough

**Upper Working Surface Shape:**

Rectangular

**Upper Working Surface Length:**

33.000 inches

**Upper Working Surface Width:**

17.000 inches

**Upper Working Surface Adjustment Feature:**

Included

**Upper Working Surface Vertical Adjustment:**

18.000 inches

**Head Vertical Adjustment:**

8.000 inches

**Spindle Type:**

Threaded end for drill chuck

**Spindle Speed Quantity:**

12

**Spindle Speed Range In Rpm:**

+225.000 to 300.000

**Upper Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Upper Working Surface:**

25.000 inches

**Voltage In Volts:**

220.0

**Phase:**

Three

**Frequency In Hertz:**

60.000

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T317-f