## NSN 3413-00-528-1932



Upright Drilling Machine - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3413-00-528-1932 **Mounting Type:** Floor **Electric Motor Power Rating:** 2.000 horsepower **Current Type:** Ac **Head Type:** Fixed **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Hand **Electric Motor Horsepower Rating:** 2.000 **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Socket Taper Size:** 3 morse **Spindle Travel Distance:** 9.000 inches **Drilling Capability:** 1 1/4 in. Drilling capacity Column Type: Box **Distance From Spindle Center To Column:** 16.000 inches Maximum Distance From Chuck/spindle Nose To Base Working Surface: 29.250 inches **Upper Working Surface Type:** 

**Upper Working Surface Shape:** Rectangular **Upper Working Surface Length:** 24.000 inches **Upper Working Surface Width:** 23.000 inches

## NSN 3413-00-528-1932

Upright Drilling Machine - Page 2 of 2



Upper Working Surface Adjustment Feature:
Included
Upper Working Surface Vertical Adjustment:
12.000 inches
Head Vertical Adjustment:
9.000 inches
Spindle Type:
Tapered socket
Spindle Speed Quantity:
4
Spindle Speed Range In Rpm:
+80.0 to 2004.0
Upper Working Surface Mounting Location:
Base
Voltage In Volts:
220.0 or 440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T317-f