NSN 3413-00-528-1934

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-00-528-1934 **Mounting Type:** Floor **Electric Motor Power Rating:** 20.000 horsepower **Current Type:** Ac **Head Type:** Sliding **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Power **Electric Motor Horsepower Rating:** 20.000 **Spindle Quantity:** 24 Main Drive Type: Electric motor **Spindle Socket Taper Size:** No 2 morse taper **Spindle Travel Distance:** 16.625 inches **Base Working Surface Length:** 46.000 inches **Base Working Surface Width:** 39.000 inches **Drilling Capability:** 0.422 in aluminum **Column Type:** Box **Distance Between Spindle Centers:** 16.750 inches **Distance From Spindle Center To Column:** 26.000 inches **Base Working Surface Type:** Slotted w/coolant trough

Base Working Surface Shape:Rectangular

NSN 3413-00-528-1934Upright Drilling Machine - Page 2 of 2



Base Working Surface Area:
Any acceptable
Base Working Surface Mounting Location:
Base
Maximum Distance From Chuck/spindle Nose To Base Working Surface:
55.000 inches
Head Vertical Adjustment:
18.000 inches
Spindle Type:
Tapered socket
Spindle Speed Quantity:
2
Spindle Speed Range In Rpm:
+520.0 to 905.0
Voltage In Volts:
140.0
Phase:
Гhree
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
Г317-f