

View Online at <https://aerobasegroup.com/nsn/3413-00-528-8606>

Mounting Type:

Bench

Electric Motor Power Rating:

0.250 horsepower

Current Type:

Ac

Head Type:

Sliding

Fungus Resistant Treatment:

Not included

Accessory Components And Quantity:

Extension cord, 1

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Electric Motor Horsepower Rating:

0.250

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Travel Distance:

2.375 inches

Drilling Capability:

5/16 in. Drillingcapacity in mild steel

Column Type:

Round

Drill Chuck Size Accommodated:

5/16 in. Key

Distance From Spindle Center To Column:

5.875 inches

Base Working Surface Type:

Plain

Base Working Surface Shape:

Round

Base Working Surface Area:

23.748 square inches

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

10.875 inches

Upper Working Surface Type:

Plain

Upper Working Surface Shape:

Rectangular

Upper Working Surface Area:

80.500 square inches

Upper Working Surface Adjustment Feature:

Not included

Head Vertical Adjustment:

8.000 inches

Spindle Type:

Threaded end for drill chuck

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+750.0 to 6000.0

Upper Working Surface Mounting Location:

Over round table surface

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

Any acceptable

Intermediate Working Surface Type:

Plain

Intermediate Working Surface Shape:

Round

Intermediate Working Surface Diameter:

5.500 inches

Err Default:

Err default

Intermediate Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Intermediate Working Surface:

8.750 inches

Voltage In Volts:

110.0

Phase:

Single

Frequency In Hertz:

60.0

Specification Or Standard:

2 class and b style and 1 size and ii type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T317-f