## NSN 3413-00-529-0941

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-00-529-0941 **Mounting Type:** Floor **Current Type:** Ac **Head Type:** Sliding **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Power **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Socket Taper Size:** No. 4 morse taper **Spindle Travel Distance:** 11.125 inches **Drilling Capability:** 5 in. In mild steel **Column Type:** Round **Distance From Spindle Center To Column:** 14.000 inches **Base Working Surface Type:** Slotted w/coolant trough **Base Working Surface Shape:** Rectangular **Base Working Surface Mounting Location:** Base Maximum Distance From Chuck/spindle Nose To Base Working Surface: 55.500 inches **Upper Working Surface Type:** Slotted **Upper Working Surface Shape:** 

Rectangular **Upper Working Surface Length:** 24.000 inches

## **NSN 3413-00-529-0941**Upright Drilling Machine - Page 2 of 2



Upper Working Surface Width:
21.000 inches
Upper Working Surface Adjustment Feature:
ncluded
Upper Working Surface Vertical Adjustment:
10.750 inches
Head Vertical Adjustment:
17.500 inches
Spindle Type:
Tapered socket
Spindle Speed Quantity:
12
Spindle Speed Range In Rpm:
+75.0/+1250.0
Upper Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Upper Working Surface:
31.875 inches
Voltage In Volts:
220.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
Г317-f