

View Online at <https://aerobasegroup.com/nsn/3413-00-540-5421>

Mounting Type:

Bench

Electric Motor Power Rating:

0.167 horsepower

Current Type:

Ac

Head Type:

Fixed

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Electric Motor Horsepower Rating:

0.167

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Travel Distance:

2.000 inches

Base Working Surface Length:

Any acceptable

Drilling Capability:

1/4 in mild steel

Column Type:

Round

Drill Chuck Size Accommodated:

1/4 in. Key

Distance From Spindle Center To Column:

3.000 inches

Base Working Surface Type:

Plain w/coolant trough

Base Working Surface Shape:

Round

Base Working Surface Area:

Any acceptable

Base Working Surface Diameter:

5.500 inches

Base Working Surface Vertical Adjustment:

8.000 inches

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

8.000 inches

Upper Working Surface Type:

Plain

Upper Working Surface Shape:

Rectangular

Upper Working Surface Area:

Any acceptable

Upper Working Surface Length:

6.000 inches

Upper Working Surface Width:

8.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

8.000 inches

Swivel Adjustment In Deg:

90.000

Tilt Adjustment Direction And Angle In Deg:

90.0 right err-100 err-100

Spindle Type:

Solid male tapered for drill chuck

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+2450.000 to 6000.000

Upper Working Surface Mounting Location:

Over lower round table

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

7.500 inches

Voltage In Volts:

110.000

Phase:

Single

Frequency In Hertz:

60.000

Specification Or Standard:

B class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T317-f