

View Online at <https://aerobasegroup.com/nsn/3413-00-618-6582>

**Mounting Type:**

Floor

**Electric Motor Power Rating:**

5.000 horsepower

**Current Type:**

Ac

**Head Type:**

Sliding

**Fungus Resistant Treatment:**

Not included

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Included

**Feed Type:**

Power

**Electric Motor Horsepower Rating:**

5.000

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Socket Taper Size:**

No. 4 morse taper

**Spindle Travel Distance:**

12.000 inches

**Base Working Surface Length:**

24.000 inches

**Base Working Surface Width:**

23.000 inches

**Drilling Capability:**

1.500 in mild steel

**Column Type:**

Box

**Distance From Spindle Center To Column:**

14.000 inches

**Base Working Surface Type:**

Slotted w/coolant trough

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Area:**

Any acceptable

**Base Working Surface Mounting Location:**

Base

**Maximum Distance From Chuck/spindle Nose To Base Working Surface:**

48.000 inches

**Upper Working Surface Type:**

Slotted

**Upper Working Surface Shape:**

Rectangular

**Upper Working Surface Area:**

Any acceptable

**Upper Working Surface Length:**

28.000 inches

**Upper Working Surface Width:**

24.000 inches

**Upper Working Surface Adjustment Feature:**

Included

**Upper Working Surface Vertical Adjustment:**

15.000 inches

**Swivel Adjustment In Deg:**

360.0

**Tilt Adjustment Direction And Angle In Deg:**

90.0 left

**Head Vertical Adjustment:**

18.000 inches

**Spindle Type:**

Tapered socket

**Spindle Speed Quantity:**

12

**Spindle Speed Range In Rpm:**

+75.0 to 1500.0

**Upper Working Surface Mounting Location:**

Over base surface

**Maximum Distance From Chuck/spindle Nose To Upper Working Surface:**

33.000 inches

**Voltage In Volts:**

220.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T317-f