

View Online at <https://aerobasegroup.com/nsn/3413-00-881-8277>

**Mounting Type:**

Bench

**Current Type:**

Ac

**Head Type:**

Sliding

**Fungus Resistant Treatment:**

Included

**Accessory Components And Quantity:**

Hand tools, 1 set; work light, 1; drift drill morse taper no. 3, 1; coolant system, 1; extra drive belts, 1 set

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Not included

**Feed Type:**

Hand

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Socket Taper Size:**

3 morse

**Spindle Travel Distance:**

6.000 inches

**Base Working Surface Length:**

15.000 inches

**Base Working Surface Width:**

13.000 inches

**Drilling Capability:**

1 in. Drillingcapacity in cast iron

**Column Type:**

Round

**Distance From Spindle Center To Column:**

10.000 inches

**Base Working Surface Type:**

Slotted

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Mounting Location:**

Base

**Maximum Distance From Chuck/spindle Nose To Base Working Surface:**

28.000 inches

**Upper Working Surface Type:**

Slotted

**Upper Working Surface Shape:**

Rectangular

**Upper Working Surface Length:**

15.000 inches

**Upper Working Surface Width:**

13.000 inches

**Upper Working Surface Adjustment Feature:**

Included

**Swivel Adjustment In Deg:**

360.0

**Spindle Type:**

Tapered socket

**Spindle Speed Quantity:**

5

**Spindle Speed Range In Rpm:**

+280.0/+1500.0

**Upper Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Upper Working Surface:**

16.000 inches

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

2-3/8 in. Diameter quill, step pulley.

**Frequency In Hertz:**

60.0

**Specification Or Standard:**

1 type and a style and 3 size

**Departure From Cited Designator:**

As modified by accessory components and coolant system

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T317-f