

View Online at <https://aerobasegroup.com/nsn/3413-00-926-3770>

Mounting Type:

Floor

Electric Motor Power Rating:

0.500 horsepower

Current Type:

Ac

Head Type:

Fixed

Fungus Resistant Treatment:

Not included

Accessory Components And Quantity:

Switch, push button 1

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Electric Motor Horsepower Rating:

0.500

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

2 morse

Spindle Travel Distance:

4.438 inches

Base Working Surface Length:

Any acceptable

Base Working Surface Width:

Any acceptable

Drilling Capability:

0.500 in. Cast iron

Column Type:

Round

Drill Chuck Size Accommodated:

1/2 in. Key

Distance From Spindle Center To Column:

7.500 inches

Base Working Surface Type:

Slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Area:

100.000 square inches

Err Default:

Err default

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

47.250 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Rectangular

Upper Working Surface Area:

100.000 square inches

Err Default:

Err default

Upper Working Surface Length:

Any acceptable

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

42.313 inches

Swivel Adjustment In Deg:

360.0

Tilt Adjustment Direction And Angle In Deg:

40.0 right

Spindle Type:

Threaded end for drill chuck

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+680.0/+4600.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

42.313 inches

Voltage In Volts:

230.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f