

View Online at <https://aerobasegroup.com/nsn/3413-00-964-9379>

Mounting Type:

Floor

Current Type:

Ac

Head Type:

Fixed

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Power

Electric Motor Horsepower Rating:

Any acceptable

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

3 morse

Spindle Travel Distance:

Between 6.000 inches and 6.500 inches

Base Working Surface Length:

Between 14.750 inches and 18.000 inches

Base Working Surface Width:

13.500 inches

Drilling Capability:

1 in. Drilling capacity in cast iron

Column Type:

Round

Distance From Spindle Center To Column:

10.000 inches

Base Working Surface Type:

Tee slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

45.000 inches

Upper Working Surface Type:

Tee slotted w/coolant trough

Upper Working Surface Shape:

Rectangular

Upper Working Surface Length:

18.000 inches

Upper Working Surface Width:

15.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

Any acceptable

Swivel Adjustment In Deg:

360.0

Tilt Adjustment Direction And Angle In Deg:

40.0 right

Spindle Type:

Tapered socket

Spindle Speed Quantity:

5

Spindle Speed Range In Rpm:

+290.0/+2000.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

35.750 inches

Voltage In Volts:

460.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Or Standard:

2 type and a style and 3 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f