## NSN 3413-01-133-2085

Radial Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-01-133-2085 **Mounting Type:** Bench **Current Type: Current Rating In Amps:** 2.0 or 1.0 Main Drive Type: Electric motor **Column Diameter:** 3.750 inches **Spindle Socket Taper Size:** 2 morse **Spindle Travel Distance:** 17.000 inches **Maximum Distance From Spindle Center To Column:** 30.000 inches **Minimum Distance From Spindle Center To Column:** 13.000 inches **Maximum Distance From Spindle Nose To Base:** 24.188 inches **Minimum Distance From Spindle Nose To Base:** 3.062 inches **Base Working Surface Length:** 26.000 inches **Base Working Surface Width:** 18.000 inches **Spindle Speed Quantity:** Spindle Speed Range In Rpm: +175.0 to 8200.0 Voltage In Volts: 230.0 Phase: Three **Special Features:** 230/460v; head tilts 45 degrees left or right, swivels 360 deg; vertical tvl of head 20.0 in.; includes floor stand 65-863, jack shaft assembly, belt guards, v-belts 49-287 and 49-105 Frequency In Hertz: 60.0

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 3413-01-133-2085

Radial Drilling Machine - Page 2 of 2



Demilitarization:

No

Fiig:

Т317-е