NSN 3413-01-137-8543



Upright Drilling Machine - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3413-01-137-8543 **Mounting Type:** Floor **Current Type:** Ac **Head Type:** Fixed **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Power **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Socket Taper Size:** 3 morse **Spindle Travel Distance:** 8.000 inches **Base Working Surface Length:** 17.000 inches **Base Working Surface Width:** 13.000 inches **Drilling Capability:** 1 in. Drilling capacity in cast iron Column Type: Round **Distance From Spindle Center To Column:** 10.000 inches **Base Working Surface Type:** Slotted **Base Working Surface Shape:** Rectangular **Base Working Surface Mounting Location:**

Column

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

49.000 inches

Upper Working Surface Type:

Slotted

NSN 3413-01-137-8543Upright Drilling Machine - Page 2 of 2



Upper Working Surface Shape:
Rectangular
Upper Working Surface Length:
16.000 inches
Upper Working Surface Width:
12.000 inches
Upper Working Surface Adjustment Feature:
Included
Upper Working Surface Vertical Adjustment:
34.000 inches
Swivel Adjustment In Deg:
360.0
Spindle Type:
Tapered socket
Spindle Speed Range In Rpm:
+100.0/+2800.0
Upper Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Upper Working Surface:
34.000 inches
Voltage In Volts:
220.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T317-f