
Upright Drilling Machine - Page 1 of 2





| view Online at https://aerobasegroup.com/nsn/3413-01-137-6545     |
|---|
| Mounting Type:  |
| Floor   |
| Current Type:   |
| Ac  |
| Head Type:  |
| Fixed   |
| Fungus Resistant Treatment:                                       |
| Not included  |
| Radio Interference Shielding:                                     |
| Not provided  |
| Rotation Reversibility Feature:                                   |
| Not included  |
| Feed Type:  |
| Power   |
| Spindle Quantity:   |
| 1   |
| Main Drive Type:  |
| Electric motor  |
| Spindle Socket Taper Size:  |
| 3 morse   |
| Spindle Travel Distance:  |
| 8.000 inches  |
| Base Working Surface Length:                                      |
| 17.000 inches   |
| Base Working Surface Width:                                       |
| 13.000 inches   |
| Drilling Capability:  |
| 1 in. Drilling capacity in cast iron                              |
| Column Type:  |
| Round   |
| Distance From Spindle Center To Column:                           |
| 10.000 inches   |
| Base Working Surface Type:  |
| Slotted   |
| Base Working Surface Shape:                                       |
| Rectangular   |
| Base Working Surface Mounting Location:                           |
| Column  |
| Maximum Distance From Chuck/spindle Nose To Base Working Surface: |
| 49.000 inches   |
| Upper Working Surface Type:                                       |
|   |

Slotted

## NSN 3413-01-137-8543

Upright Drilling Machine - Page 2 of 2



| Upper Working Surface Shape:                                       |
|--|
| Rectangular  |
| Upper Working Surface Length:                                      |
| 16.000 inches  |
| Upper Working Surface Width:                                       |
| 12.000 inches  |
| Upper Working Surface Adjustment Feature:                          |
|  |
| Upper Working Surface Vertical Adjustment:                         |
| 34.000 inches  |
| Swivel Adjustment In Deg:  |
| 360.0  |
| Spindle Type:  |
| Tapered socket   |
| Spindle Speed Range In Rpm:  |
| +100.0/+2800.0   |
| Upper Working Surface Mounting Location:                           |
| Column   |
| Maximum Distance From Chuck/spindle Nose To Upper Working Surface: |
| 34.000 inches  |
| Voltage In Volts:  |
| 220.0  |
| Phase:   |
| Three  |
| Frequency In Hertz:  |
| 60.0   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Fiig:  |
| T317-f   |