## NSN 3413-01-166-4278

Radial Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-01-166-4278

| Manustina Tomas   |
|---|
| Mounting Type:  |
| Floor   |
| Current Type:   |
| Ac  |
| Main Drive Type:  |
| Electric motor  |
| Arm Size:   |
| 2.000 feet  |
| Column Diameter:  |
| 6.297 inches  |
| Spindle Socket Taper Size:  |
| 4 morse   |
| Spindle Travel Distance:  |
| 5.900 inches  |
| Maximum Distance From Spindle Center To Column:                               |
| 22.812 inches   |
| Minimum Distance From Spindle Center To Column:                               |
| 11.812 inches   |
| Maximum Distance From Spindle Nose To Base:                                   |
| 23.047 inches   |
| Minimum Distance From Spindle Nose To Base:                                   |
| 8.281 inches  |
| Base Working Surface Length:  |
| 34.625 inches   |
| Base Working Surface Width:   |
| 24.000 inches   |
| Drilling Capability:  |
| 1-1/4 in. Drill capacity in steel and a 1-1/2 in. Drill capacity in cast iron |
| Spindle Speed Quantity:   |
| 12  |
| Spindle Speed Range In Rpm:   |
| +80.0 to 2300.0   |
| Voltage In Volts:   |
| 230.0 or 460.0  |
| Phase:  |
| Three   |
| Frequency In Hertz:   |
| 60.0  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| OTHE OT WIEdburg.   |

--

## NSN 3413-01-166-4278

Radial Drilling Machine - Page 2 of 2



Demilitarization:

No

Fiig:

Т317-е