NSN 3413-01-174-9328

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-01-174-9328 **Mounting Type:** Floor **Current Type:** Ac **Head Type:** Fixed **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Hand **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Socket Taper Size:** 3 morse **Spindle Travel Distance:** 7.000 inches **Base Working Surface Length:** 25.000 inches **Base Working Surface Width:** 18.000 inches **Drilling Capability:** 1.125 in. Drilling capacity in mild steel Column Type: Round **Distance From Spindle Center To Column:** 10.062 inches **Base Working Surface Type:** Slotted w/coolant trough **Base Working Surface Shape:** Rectangular **Base Working Surface Mounting Location:** Column Spindle Type:

Tapered socket **Spindle Speed Quantity:** 1

NSN 3413-01-174-9328

Upright Drilling Machine - Page 2 of 2



| Spindle Speed Range In Rpm: |
|-----------------------------|
| +80.0/+1200.0 |
| Voltage In Volts: |
| 230.0 |
| Phase: |
| Three |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: T317-f