NSN 3413-01-180-0328

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-01-180-0328 **Mounting Type:** Floor **Electric Motor Power Rating:** 3.000 horsepower **Current Type:** Ac **Head Type:** Fixed **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Hand **Electric Motor Horsepower Rating:** 3.000 **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Socket Taper Size:** 3 morse **Spindle Travel Distance:** 5.125 inches **Base Working Surface Length:** 28.000 inches **Base Working Surface Width:** 18.500 inches **Drilling Capability:** 1-1/2 in. Drilling capacity in cast iron **Column Type:** Round **Distance From Spindle Center To Column:** Any acceptable **Base Working Surface Type:** Slotted

Slotted

Base Working Surface Shape:
Rectangular

Base Working Surface Area:
Any acceptable

NSN 3413-01-180-0328Upright Drilling Machine - Page 2 of 2



Err Default:
Err default
Base Working Surface Mounting Location:
Base
Maximum Distance From Chuck/spindle Nose To Base Working Surface:
45.000 inches
Upper Working Surface Type:
Slotted
Upper Working Surface Shape:
Rectangular
Upper Working Surface Area:
450.000 square inches
Upper Working Surface Length:
25.000 inches
Upper Working Surface Width:
18.000 inches
Upper Working Surface Adjustment Feature:
Not included
Spindle Type:
Tapered socket
Spindle Speed Quantity:
1
Spindle Speed Range In Rpm:
+85.0/+1460.0
Upper Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Upper Working Surface:
30.750 inches
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T317-f