

View Online at <https://aerobasegroup.com/nsn/3413-01-210-1975>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Head Type:**

Fixed

**Fungus Resistant Treatment:**

Not included

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Not included

**Feed Type:**

Hand

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Socket Taper Size:**

3 morse

**Spindle Travel Distance:**

6.500 inches

**Base Working Surface Length:**

15.500 inches

**Base Working Surface Width:**

13.000 inches

**Drilling Capability:**

1-1/2 in. Drilling capacity in mild steel

**Column Type:**

Round

**Distance From Spindle Center To Column:**

9.500 inches

**Base Working Surface Type:**

Slotted

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Area:**

201.500 square inches

**Base Working Surface Vertical Adjustment:**

43.375 inches

**Base Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Base Working Surface:**

43.375 inches

**Upper Working Surface Type:**

Slotted

**Upper Working Surface Shape:**

Rectangular

**Upper Working Surface Area:**

429.000 square inches

**Upper Working Surface Length:**

22.000 inches

**Upper Working Surface Width:**

19.500 inches

**Upper Working Surface Adjustment Feature:**

Included

**Upper Working Surface Vertical Adjustment:**

20.000 inches

**Spindle Type:**

Tapered socket

**Spindle Speed Quantity:**

1

**Spindle Speed Range In Rpm:**

+200.0 to 1300.0

**Maximum Distance From Chuck/spindle Nose To Upper Working Surface:**

33.125 inches

**Voltage In Volts:**

220.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T317-f