

View Online at <https://aerobasegroup.com/nsn/3413-01-210-1975>

Mounting Type:

Floor

Current Type:

Ac

Head Type:

Fixed

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Not provided

Rotation Reversibility Feature:

Not included

Feed Type:

Hand

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

3 morse

Spindle Travel Distance:

6.500 inches

Base Working Surface Length:

15.500 inches

Base Working Surface Width:

13.000 inches

Drilling Capability:

1-1/2 in. Drilling capacity in mild steel

Column Type:

Round

Distance From Spindle Center To Column:

9.500 inches

Base Working Surface Type:

Slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Area:

201.500 square inches

Base Working Surface Vertical Adjustment:

43.375 inches

Base Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

43.375 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Rectangular

Upper Working Surface Area:

429.000 square inches

Upper Working Surface Length:

22.000 inches

Upper Working Surface Width:

19.500 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

20.000 inches

Spindle Type:

Tapered socket

Spindle Speed Quantity:

1

Spindle Speed Range In Rpm:

+200.0 to 1300.0

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

33.125 inches

Voltage In Volts:

220.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f