

View Online at <https://aerobasegroup.com/nsn/3413-01-253-8071>

Mounting Type:

Floor

Current Type:

Ac

Head Type:

Fixed

Fungus Resistant Treatment:

Not included

Radio Interference Shielding:

Provided

Rotation Reversibility Feature:

Not included

Feed Type:

Power

Spindle Quantity:

1

Main Drive Type:

Electric motor

Spindle Socket Taper Size:

3 morse

Spindle Travel Distance:

Between 0.500 inches and 6.000 inches

Base Working Surface Length:

16.250 inches

Base Working Surface Width:

13.500 inches

Drilling Capability:

1 in. Stl, 1-1/8 cast iron

Column Type:

Round

Distance From Spindle Center To Column:

11.875 inches

Base Working Surface Type:

Tee slotted

Base Working Surface Shape:

Rectangular

Base Working Surface Area:

219.375 square inches

Base Working Surface Mounting Location:

Base

Maximum Distance From Chuck/spindle Nose To Base Working Surface:

44.500 inches

Upper Working Surface Type:

Plain w/coolant trough

Upper Working Surface Shape:

Rectangular

Upper Working Surface Area:

288.000 square inches

Upper Working Surface Length:

18.000 inches

Upper Working Surface Width:

16.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

34.250 inches

Swivel Adjustment In Deg:

360.0

Tilt Adjustment Direction And Angle In Deg:

90.0 right

Spindle Type:

Tapered socket

Spindle Speed Quantity:

8

Spindle Speed Range In Rpm:

+200.0/+2000.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

34.250 inches

Voltage In Volts:

230.0

Phase:

Single

Special Features:

Tilt adj left and right 90 deg

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T317-f