NSN 3413-01-312-2376

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-01-312-2376

Mounting Type:
Bench
Current Type:
Ac
Fungus Resistant Treatment:
Not included
Radio Interference Shielding:
Not provided
Rotation Reversibility Feature:
Not included
Feed Type:
Hand
Spindle Quantity:
1
Main Drive Type:
Electric motor
Spindle Socket Taper Size:
2 morse
Spindle Travel Distance:
4.375 inches
Drilling Capability:
5/8 in. Drilling capacity in mild steel
Column Type:
Round
Drill Chuck Size Accommodated:
5/8 in. Keys
Distance From Spindle Center To Column:
17.500 inches
Base Working Surface Type:
Slotted
Base Working Surface Shape:
Rectangular
Base Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Base Working Surface:
24.500 inches
Head Vertical Adjustment:
17.000 inches
Spindle Type:
Threaded end for drill chuck
Spindle Speed Quantity:

16

NSN 3413-01-312-2376Upright Drilling Machine - Page 2 of 2



Spindle Speed Range In Rpm:
+260.0/+3650.0
Voltage In Volts:
115.0
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T317-f