

View Online at <https://aerobasegroup.com/nsn/3413-01-369-0682>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Head Type:**

Fixed

**Fungus Resistant Treatment:**

Not included

**Accessory Components And Quantity:**

Belt and pulley guard 1, belt 1, motor pulley 1, 5/8 in. Bore, self locking depth stop 1, depth stop 1, depth gage 1, self-ejecting chuck key 1, motor 1, controls 1, no. 15-010 safety collar for head 1

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Not included

**Feed Type:**

Hand

**Electric Motor Horsepower Rating:**

0.750

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Travel Distance:**

6.000 inches

**Base Working Surface Length:**

14.000 inches

**Base Working Surface Width:**

11.250 inches

**Drilling Capability:**

1/2 in. Drilling capacity in mild steel

**Column Type:**

Round

**Drill Chuck Size Accommodated:**

1/2 in. Keys

**Distance From Spindle Center To Column:**

8.875 inches

**Base Working Surface Type:**

Tee slotted

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Area:**

157.500 square inches

**Base Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Base Working Surface:**

47.000 inches

**Upper Working Surface Type:**

Slotted w/center hole

**Upper Working Surface Shape:**

Rectangular

**Upper Working Surface Area:**

154.000 square inches

**Upper Working Surface Length:**

14.000 inches

**Upper Working Surface Width:**

11.000 inches

**Upper Working Surface Adjustment Feature:**

Included

**Upper Working Surface Vertical Adjustment:**

43.125 inches

**Swivel Adjustment In Deg:**

90.0

**Tilt Adjustment Direction And Angle In Deg:**

90.0 left

**Spindle Type:**

Solid male tapered for drill chuck

**Spindle Speed Quantity:**

6

**Spindle Speed Range In Rpm:**

+425.0/+5500.0

**Upper Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Upper Working Surface:**

43.125 inches

**Voltage In Volts:**

230.0

**Phase:**

Three

**Special Features:**

B24 volt push button station, magnetic starter, transformer and 3-leg overload protection (lvc) four extra large spindle bearings, efficient variable speed drive, quick-release, adjustable motor mount

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T317-f