

View Online at <https://aerobasegroup.com/nsn/3413-01-372-8681>

**Mounting Type:**

Floor

**Electric Motor Power Rating:**

1.000 horsepower

**Current Type:**

Ac

**Head Type:**

Fixed

**Fungus Resistant Treatment:**

Included

**Radio Interference Shielding:**

Not provided

**Rotation Reversibility Feature:**

Not included

**Feed Type:**

Power

**Electric Motor Horsepower Rating:**

1.000

**Spindle Quantity:**

1

**Main Drive Type:**

Electric motor

**Spindle Travel Distance:**

5.000 inches

**Drilling Capability:**

11/1

**Column Type:**

Round

**Drill Chuck Size Accommodated:**

1/2 in. Keys

**Distance From Spindle Center To Column:**

10.250 inches

**Base Working Surface Type:**

Plain w/coolant trough

**Base Working Surface Shape:**

Rectangular

**Base Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Base Working Surface:**

45.750 inches

**Upper Working Surface Type:**

Slotted w/center hole

**Upper Working Surface Shape:**

Rectangular

**Upper Working Surface Length:**

20.500 inches

**Upper Working Surface Width:**

16.000 inches

**Upper Working Surface Adjustment Feature:**

Included

**Upper Working Surface Vertical Adjustment:**

34.750 inches

**Swivel Adjustment In Deg:**

90.0

**Tilt Adjustment Direction And Angle In Deg:**

90.0 right

**Spindle Type:**

Solid male tapered for drill chuck

**Spindle Speed Quantity:**

10

**Spindle Speed Range In Rpm:**

+385.0/+4250.0

**Upper Working Surface Mounting Location:**

Column

**Maximum Distance From Chuck/spindle Nose To Upper Working Surface:**

34.750 inches

**Voltage In Volts:**

110.0 or 230.0

**Phase:**

Single

**Special Features:**

Interference-free guard; self-closing oil cup; quick conversion pulleys;

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T317-f