

View Online at <https://aerobasegroup.com/nsn/3415-00-529-0315>

**Current Type:**

Ac

**Furnished Items And Quantity:**

Adapte for collets smaller than 1/2 in., 1 and belts, drive work load spindle, 2 and set collets, 7 ea taper nos. 5-7-9 b and /in symbol form/, s, and numbers nos. 1-2-3-4 morse taper, 1 and set collets, 19 ea straight cylindrical in increments of 1/8, 3/16, 1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1, 1-1/16, 1-1/8, 1-3/16, 1-1/4 in., 1 and gage, center ring work head spindle, 1 and gage, centering, wheel head tooth rest, 1 and index device, 1 and guard, grinding wheel, 1 and set, operating instructions, 1 and set 3 plates, index for spiral lead mechanism, 1 and support, front stock and diamond holder, 1 and support, lower stock, 1 and support, adjustable tail center, 1 and set, wrench, 1 and pulleys, motor drive w/matching belts, 2

**Horsepower Rating:**

0.33

**Design Type:**

Universal

**Table Length:**

12.000 inches

**Table Width:**

8.000 inches

**Power Source:**

Electric motor

**Mounting Type For Which Designed:**

Floor

**Maximum Rated Swing:**

12.000 inches

**Distance Between Head Stock And Tail Stock Centers:**

6.000 inches

**Table Type:**

Swivel

**Table Longitudinal Travel:**

5.750 inches

**Table Swivel Adjustment In Deg:**

235.0

**Wheel Head Type:**

Horizontal

**Wheel Head Horizontal Travel:**

7.500 inches

**Wheel Head Vertical Adjustment:**

4.250 inches

**Maximum Distance From Wheel Head Spindle Center/face To Table Top:**

6.000 inches

**Voltage In Volts:**

110.0 and 115.0 and 220.0 and 230.0 and 550.0

**Phase:**

Two or three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T284-b