

View Online at <https://aerobasegroup.com/nsn/3415-00-529-0950>

Current Type:

Ac or dc

Center To Center Distance:

72.000 inches

Furnished Items And Quantity:

Control cabinet part no. N6344; wrenches-ratchet reversing w/special gear for 1 1/16in. Drive, 2; wrenches-socket t-handle, 2; screwdrivers no. 2 and no. 3, 2; wrenches-flare nut, 4; wrenches-spanner 2 15/16in., 2; screw-socket set 5/16in. Drive, 1; screw-socket set 3/8in. Drive, 1; screw-socket set 7/16in. Drive, 1; screw-socket set 1/2in. Drive, 1; wrenches-special, 2; wrench-pulling, off wrench, 1; guards, 2

Current Rating In Amps:

20.5 and 10.3 and 12.7 and 8.6 and 4.3 and 15.0 and 7.5 and 2.0 and 1.0

Horsepower Rating:

7.50

Design Type:

Universal

Power Source:

Electric motor

Maximum Rated Swing:

53.000 inches

Wheel Head Swivel Adjustment:

90 degrees right and left

Wheel Maximum Diameter:

20.000 inches

Wheel Head Attachment Diameter And Type:

8.500 inches spindle

Head Stock Swivel Adjustment:

360 deg

Voltage In Volts:

220.0 and 440.0 and 350.0

Phase:

Three

Special Features:

Wheelhead drive motor; workhead drive motor; internal grinding attachmentmotor; hydraulic system pump motor; coolant motor

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T284-b