

View Online at <https://aerobasegroup.com/nsn/3415-00-684-5703>

Current Type:

Ac

Furnished Items And Quantity:

Chuck, ind.6 in., 1 and chuck, univ., 4 in., 1 and dr.Belts, set, 1 and gear cutter grinding attachment for 7/16by2 in.Holes to 1-3/16by5 in.Holes, 1 and small end mill grinding attachment, 1 and spring collet, straight bore size, 3/16, 1/4, 5/16, 3/8, 7/16, 1/2, 5/8, 3/4, 1 in., 1 and sur.Grinding attachments, 1 and wheel, abrasive, cuptype flaring, 3by2-1/4by5/8 in., grain 60, gr.K, flaring, 5by1-1/2by5/8 in., grain 46, gr.K, vitrified bond, 6 and wheel abrasive, dish type, 6by3/4by5/8 in., grain 46, gr.K, vitrified bond, 6 and wheel abrasive, straight, 3by3/16by5/8 in., 6by3/8by5/8 in., grain 60, gr.H6, vitrified bond, 6 and wheel, abrasive, rubbed bond, cutoff, 8by1/16by5/8 in.

Horsepower Rating:

0.75

Design Type:

Universal

Table Length:

42.000 inches

Table Width:

6.000 inches

Power Source:

Electric motor

Mounting Type For Which Designed:

Floor

Maximum Rated Swing:

10.000 inches

Distance Between Head Stock And Tail Stock Centers:

32.000 inches

Table Type:

Swivel

Distance Between Tail Stocks:

34.000 inches

Table Longitudinal Travel:

20.000 inches

Table Cross Travel:

8.000 inches

Table Swivel Adjustment In Deg:

180.0

Wheel Head Type:

Horizontal

Wheel Head Swivel Adjustment:

360 deg

Wheel Head Vertical Adjustment:

8.000 inches

Maximum Distance From Wheel Head Spindle Center/face To Table Top:

10.500 inches

Voltage In Volts:

208.0

Phase:

Frequency In Hertz:

60.0

Specification Or Standard:

1 type and 2 size

Departure From Cited Designator:

Bmyz, bnbc, ardq, ardr, bnbd, bbnf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-b