

View Online at https://aerobasegroup.com/nsn/3415-01-212-6468

| Current Type: Ac Spindle Diameter: 0.625 inches Horsepower Rating: 0.5 Power Source: Electric motor Mounting Type For Which Designed: Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle End Type: Double Spindle Speed In Rpm: 3600.0 Maximum Wheel Diameter Accommodated: 7.000 inches Maximum Wheel Thickness Accommodated: 1.000 inches Mork Rest Design: Tilted Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: 60.0 |
|---|
| Spindle Diameter:0.625 inchesHorsepower Rating:0.5Power Source:Electric motorMounting Type For Which Designed:BenchSpindle End Type:DoubleSpindle Speed In Rpm:3600.0Maximum Wheel Diameter Accommodated:7.000 inchesMaximum Wheel Thickness Accommodated:1.000 inchesWork Rest Design:TiltedVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| 0.625 inches Horsepower Rating: 0.5 Power Source: Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle Speed In Rpm: 3600.0 Maximum Wheel Diameter Accommodated: 7.000 inches Maximum Wheel Thickness Accommodated: 1.000 inches Vork Rest Design: Tilted Voltage In Volts: 115.0 and 230.0 Phase: Single |
| Horsepower Rating: 0.5 Power Source: Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle Speed In Rpm: 3600.0 Maximum Wheel Diameter Accommodated: 7.000 inches Maximum Wheel Thickness Accommodated: 1.000 inches Mork Rest Design: Tilted Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| 0.5 Power Source: Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle Speed In Rpm: 3600.0 Maximum Wheel Diameter Accommodated: 7.000 inches Maximum Wheel Thickness Accommodated: 1.000 inches Mork Rest Design: Titled Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| Power Source:Electric motorMounting Type For Which Designed:BenchBenchSpindle End Type:DoubleSpindle Speed In Rpm:3600.0Maximum Wheel Diameter Accommodated:7.000 inchesMaximum Wheel Thickness Accommodated:1.000 inchesWork Rest Design:TiltedVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| Electric motor Mounting Type For Which Designed: Bench Bench Spindle End Type: Double Spindle Speed In Rpm: 3600.0 Maximum Wheel Diameter Accommodated: 7.000 inches Maximum Wheel Thickness Accommodated: 1.000 inches Mork Rest Design: Tilted Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| Mounting Type For Which Designed:BenchSpindle End Type:DoubleSpindle Speed In Rpm:3600.0Maximum Wheel Diameter Accommodated:7.000 inchesMaximum Wheel Thickness Accommodated:1.000 inchesWork Rest Design:TiltedVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| BenchSpindle End Type:DoubleSpindle Speed In Rpm:3600.0Maximum Wheel Diameter Accommodated:7.000 inchesMaximum Wheel Thickness Accommodated:1.000 inchesWork Rest Design:TiltedVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| Spindle End Type:DoubleSpindle Speed In Rpm:3600.0Maximum Wheel Diameter Accommodated:7.000 inchesMaximum Wheel Thickness Accommodated:1.000 inchesWork Rest Design:TiltedVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| Double Spindle Speed In Rpm: 3600.0 Maximum Wheel Diameter Accommodated: 7.000 inches Maximum Wheel Thickness Accommodated: 1.000 inches Mork Rest Design: Titted Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| Spindle Speed In Rpm:3600.0Maximum Wheel Diameter Accommodated:7.000 inchesMaximum Wheel Thickness Accommodated:1.000 inchesVork Rest Design:1.000 inchesVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| 3600.0 Maximum Wheel Diameter Accommodated: 7.000 inches Maximum Wheel Thickness Accommodated: 1.000 inches Work Rest Design: Tilted Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| Maximum Wheel Diameter Accommodated:7.000 inchesMaximum Wheel Thickness Accommodated:1.000 inchesWork Rest Design:TiltedVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| 7.000 inches Maximum Wheel Thickness Accommodated: 1.000 inches Work Rest Design: Tilted Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| Maximum Wheel Thickness Accommodated:1.000 inchesWork Rest Design:TiltedVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| 1.000 inches Work Rest Design: Tilted Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| Work Rest Design:TiltedVoltage In Volts:115.0 and 230.0Phase:SingleFrequency In Hertz: |
| Tilted Voltage In Volts: 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| 115.0 and 230.0 Phase: Single Frequency In Hertz: |
| Single Frequency In Hertz: |
| Frequency In Hertz: |
| |
| 60.0 |
| 60.0 |
| Quantity: |
| 1 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| Т284-а |
| |