

View Online at <https://aerobasegroup.com/nsn/3415-01-357-2021>

Current Type:

Ac

Spindle Diameter:

1.000 inches

Current Rating In Amps:

300.0

Horsepower Rating:

5.0

Power Source:

Electric motor

Mounting Type For Which Designed:

Floor

Wheel Maximum Diameter:

8.000 inches

Spindle Position:

Horizontal

Work Surface Length:

18.000 inches

Work Surface Width:

6.000 inches

Work Surface Longitudinal Travel:

19.000 inches

Work Surface Cross Travel:

6.500 inches

Work Surface Feed Method:

Power

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

3 axis; z axis 15.5 in.; feed rate variable from .1 to 200 rpm; safety wheel guard; cnc; dc power supply; floor stand nema 12 to house lectropak components; electrochemical process; auto. Lubrication; spindle speed 2700 rpm; max feed 200 ipm; wheel 1.25 in. Wd; wheel hole 1.25 in.; 50 gal. Electrolyte tank with 1/2 hp pump; mist collector mc3

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-c