Utility Grinding And Buffing Machine - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3415-01-382-0731

Current Type: Ac **Spindle Diameter:** 0.625 inches **Furnished Items And Quantity:** Multi-purpose tool rest, 2; adjustable eyeshield, 2; adjustable spark deflector, 2; wheel guard, 2; removable side plate, 2; water pot, 1; dust collection adapters, 2; wheel, coarse, 1; wheel, medium, 1 **Horsepower Rating:** 0.5 **Power Source:** Electric motor Mounting Type For Which Designed: Bench Spindle End Type: Double Spindle Speed In Rpm: 3450.0 Maximum Wheel Diameter Accommodated: 7.000 inches **Maximum Wheel Thickness Accommodated:** 1.000 inches Work Rest Design: Tilted

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Totally enclosed motor rated for continuous duty; lifetime, sealed, ball bearing construction; small diameter motor frame; meets all osha standards; height 13 1/8 in.; width 22 3/8 in.; front to back 11 5/8 in.; weight 41 pounds; three phase electricals will be supplied wired for 230 volt unless 460 volt is specified; wire wheel is available when specified upon ordering

Frequency In Hertz:

60.0

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T284-a